

DucoVent Premium Trim

High-end premium vent



Also as 'trimless' integration



The **DucoVent Premium Trim** is applicable for **both supply and extraction** with a **maximum flow rate of 50 m³/h for supply and 75 m³/h for extraction**.

Thanks to a **minimal mounting height** and **paintable visible parts**, the valve virtually merges into the ceiling. The **thoughtful design** ensures a **diffuse air supply via the Coanda effect** and thus guarantees optimum comfort. Aesthetics and quality in one product! A perfect combination with DUCO's high-quality ventilation solutions!



SCAN & DISCOVER



Discover more about the **DucoVent Premium Trim!**



DucoVent Premium Trimless

The **DucoVent Premium Trimless** is the design vent par excellence and can be used for **both supply and extraction** with a **maximum flow rate of 50 m³/h**.

A **'trimless' integration in the plasterwork** makes the vent virtually invisible. The thoughtful design ensures a **diffuse air supply via the Coanda effect** and thus guarantees optimum comfort. Aesthetics and quality in one product!

SCAN & DISCOVER



Discover more about the **DucoVent Premium Trimless!**

DucoVent Premium Trim – Technical Specifications

Feature	Specification
Item Number	0000-5004
Dimensions	Ø145 mm
Mounting Height	1.5 mm (minimal)
Scope of Application	Supply & extraction
Connection	Ø125 mm
Sealing	Rubber mounting ring
Mounting	Ceiling or wall (min. 180 cm above floor, 35 cm from walls)
Maximum Flow Rate (Supply)	50 m ³ /h
Maximum Flow Rate (Extraction)	75 m ³ /h
Adjustment	34 adjustment positions
Material	Plastic Rubber
Colour	White (paintable with synthetic primer)
Weight	140 g